



AX3 LightDrop



Optical

Colours
RGBW

Total LED power
15W

Luminous Flux
390Lm

Emittance (@2m)
1300Lx

Strobe
0-25Hz

Beam Angle
13°

Pixels
1

Electrical

Battery
LG Chem Lithium-ion

Battery Lifetime
70% after 300 cycles

Battery Runtime
Up to 20 hours

Charging time (nominal)
7 Hours

Input Voltage (charger)
90-264V 47-63Hz

Input voltage (light)
5V 2.5A

Control

Wireless Modules
865-870MHz
902-928MHz
2.4GHz

Range
300m | 330 Yards

Wireless DMX
CRMX & others, excluding W-DMX G5, City Theatrical

Construction

Housing
ABS

IP Rating
IP65










Relative humidity
0-100%

Operating Temperature
0-40 °C
32-104 °F

Weight
0.679kg
1.4Lbs

Dimensions (with bracket)
120 x 59 x 114 (mm)
7.4 x 2.3 x 4.4 (inches)

Accessories

-  **Charger**
AX3-CHR (Included)
-  **Hooks (3)**
AX3-EBLT (Included)
-  **Rubber Feet (4)**
AX3-FEET (Included)
-  **Bracket**
AX3-STA (Included)
-  **30° diffuser**
AX3-DDSK30 (Included)
-  **120° diffuser**
AX3-DDSK-120 (Included)
-  **Wallwash diffuser**
AX3-WWDSK
-  **Diffuser dome**
AX3-DDM
-  **Charging case**
AX3-CHRCSE



3.8" screw thread
Compatible with Manfrotto
Bolt type 013

