



DATASHEET

S21

World-class mixing at an astonishing price

OVERVIEW

The DiGiCo S21 is a 48 channel mixing console with 21 physical faders and 2 x 10" multitouch screens. Using state-of-the-art FPGA technology, the S21 provides the same high quality audio as the legendary SD-Range.



KEY FEATURES

48 Flexi Input Channels (mono/stereo)

16 Flexi Aux / Sub-Group Busses (mono/stereo)

10 x 8 Matrix with full processing

Fully assignable channel layout

24 local mic/line inputs and 12 line outputs

2 DMI slots to expand the I/O as desired

Snapshots for seamlessly changing many parameters at once

Offline software

iPad control

Compatible with the DMI-AMM for automatic microphone mixing

OSC control of snapshots



DiGiCo S-Series

DiGiCo consoles are used on many of the biggest live sound tours and events around the world and the compact S-Series made this pedigree of audio performance available to every part of the industry, with Stealth Digital Processing™ introducing a new standard of audio quality, power and flexibility not seen before at its price point.

TECHNICAL SPECIFICATIONS

WORKSURFACE

21 x 100mm touch-sensitive, motorised faders
2 x 10" Multi-touch screens
2 x 24-Segment Master/Solo LED meters
1 x ¼" Headphone socket
1 x 3.5mm Headphone socket
1 x USB 2.0 slot
26 x Touch-sensitive rotaries

REAR

1 x PSU
24 x XLR Mic/Line Inputs
12 x XLR Line Outputs
1 x XLR AES/EBU Input (2 x channels)
1 x XLR AES/EBU Output (2 x channels)
1 x GPI ¼" Jack
1 x GPO ¼" Jack
1 x UB MADI (USB Type B Audio I/O interface for recording and playback of up to 48 channels)
1 x Word Clock I/O BNC
1 x DVI port
2 x Ethernet ports
2 x USB 2.0 slots
2 x DMI slots (up to 64 I/O per slot)

OPTIONS

Flightcase
Compatible DMI Cards: A3232 / ADC / AES / AMM / Aviom / DAC / Dante / Dante64@96 / Hydra 2 / KLANG (audio only) / MADI B / MADI C / ME / MIC / Waves

SIGNAL PROCESSING

48 Flexi Input Channels (Mono or Stereo)

- Analogue Gain
- Phase Inversion Control
- Gain Tracking
- Digital Trim (-40dB to +40dB)
- Variable Delay (0ms to 682ms)
- DiGiTube*
- HPF/LPF (-24dB/Oct)
- 4 Band Parametric EQ / Dynamic EQ*
- DYN 1: Compressor, Multiband Compressor*
- DYN 2: Compressor with Side-Chain, Keyed Gate, Ducker
- EQ/Dyn Order Control
- 2 Insert Points per Channel
- Channel Mute
- Channel Direct Output (pre-mute, pre-fade, post-fade)
- Record Send and Return

16 Flexi Aux/Sub-Group Busses (Mono or Stereo)

- Phase Inversion Control
- Digital Trim (-40dB to +40dB)
- Variable Delay (0ms to 682ms)
- DiGiTube*
- HPF/LPF (-24dB/Oct)
- 4 Band Parametric EQ / Dynamic EQ*
- DYN 1: Compressor, Multiband Compressor*
- DYN 2: Compressor with Side-Chain, Keyed Gate, Ducker
- EQ/Dyn Order Control
- 2 Insert Points per Channel
- Channel Mute
- Channel Direct Outputs

1 LR Master Buss

10 input x 8 output Full Processing Matrix

10 Control Groups (CGs)

2 Solo Busses (Stereo)

16 x 32-band GEQs


8 x Internal Stereo FX Processors

- Reverbs
- Delays
- Audio Enhancer
- Choruses
- Flanger
- Stereo Thicken

* Up to 21 DiGiTubes

* Up to 21 Dynamic EQs

* Up to 21 Multiband Compressors



A&E SPECIFICATION

The DiGiCo S21 shall have 21 faders split into 2 worksurface sections of 10 faders plus a master fader. Each worksurface section shall have up to 6 layers of banks of 10 channels. The bank and channel layout shall be fully customisable, including the assignment of the master fader. The console shall be capable of 48 flexi input channels (mono/stereo), 16 flexi Aux/Sub-group Busses (mono/stereo), a LR Master Buss, 10 VCA style or mute group style Control Group channels, 2 Solo Busses, and a 10 input x 8 output full processing Matrix. All processing paths shall have full processing including Tube emulation, Dynamic EQ and Multiband Compression. Tube emulation, Dynamic EQ and Multiband Compression shall all be limited to 21 instances of each per session. All processing shall be internal and FPGA-based. An internal FX rack with 8 stereo slots shall allow users to pick from 23 different FX. An internal set of 16 32-band GEQs shall also be accessible.

2 x 10" multitouch screens shall be provided to show channel strips and the master controls. There shall also be a set of touch sensitive rotaries with integrated switches and HTL colour encoded rings below each screen and another set of master rotaries to control global parameters. The front panel shall also have a physical control to adjust the headphone level, as well as physical buttons to change the snapshot, toggle the spill set and show the overview screen. The front worksurface shall also have a USB 2.0 slot and a 1/4" headphone socket as well as a 3.5mm headphone socket.

The rear panel shall have 24 Mic/Line inputs, 12 line outputs, 1 AES/EBU input (2 channels) and 1 AES/EBU output (2 channels). It shall also have an inbuilt UB MADI (USB Type B audio I/O interface for recording and playback of up to 48 channels). The other connectors on the rear of the console shall be 1 GPI, 1 GPO, Word clock in/out, a DVI port, 2 USB 2.0 slots, 2 ethernet ports and 2 DMI slots.

The dimensions of the S21 shall be: 763 (w) x 586 (d) x 295 (h) mm
The weight of the S21 shall be: 19 kg
The DiGiCo S21 shall be supplied with a dust cover.

AUDIO SPECIFICATIONS




Sample Rate: 48kHz or 96kHz
Processing Delay: 2ms Typical @ 48K (60 Stereo Channels, Stage input Through L-R Buss to Stage Output) 1.1ms @ 96k
Internal Processing: Up to 40-bit, Floating Point
A>D & D>A: 24-bit Converter Bit Depth
Frequency Response: +/- 0.6dB (20Hz – 20kHz)
THD: <0.05% @ Unity Gain,; 10dB Input @ 1kHz
Channel Separation: Better Than 90dB: (40Hz-15kHz)
Residual Output Noise: <90dBu Typical (20Hz-20kHz)
Microphone Input: Better Than -126dB: Equivalent Noise
Maximum Output Level: +22dBu
Maximum Input Level: +22dBu

In a world as competitive for engineers as it is for console owners, you want the best tools you can lay your hands on. You also want a console and audio tools as well thought out for every major application as they are designed for the art and science of sound engineering.



LINE DRAWING

All dimensions in mm



PHYSICAL

Dimensions: 763mm (w) x 586mm (d) x 295mm (h)

Weight: 19kg (65kg with optional flightcase)

Flightcase: 846mm (w) x 467mm (d) x 866mm (h) (Optional)

Power Requirements: 90-264 VAC, 47-63Hz Auto Sensing. 208 watts, 232VA

Product Code: X-S21-WS

DiGiCo HQ

Unit 10 Silverglade Business Park Leatherhead Road, Chessington,
Surrey, KT9 2QL, United Kingdom
info@digiconsoles.com

©DiGiCo 2019. All brand and product names are copyright to their respective owners
E&OE

www.digico.biz

DiGiCo
www.digico.biz